



SURFACE MOUNTED CEILING LUMINAIRE FOR  
PASSAGE WAYS, CABINS, ACCOMMODATION  
AND PUBLIC AREAS

<b>Design</b>	According to rules of maritime classification societies and relevant standards
<b>Housing</b>	Galvanized steel, powder coated white (RAL9016)
<b>Diffuser</b>	Opal polycarbonate, impact-proof
<b>Mounting</b>	4 mounting holes Ø 5.8 mm
<b>Cable entry</b>	4 inlets for cables max. Ø 11 mm
<b>Protection class</b>	IP43
<b>Weight</b>	3.0 kg
<b>Light source</b>	Linear LP LED modules
<b>Wattage</b>	Max. 20 W / HO: max. 38 W
<b>CCT (color)</b>	3,000 K or 4,000 K
<b>Luminous flux</b>	1,500 lm / HO: 3,400 lm
<b>CRI</b>	≥ 80
<b>Voltage</b>	220–240 V AC
<b>Frequency</b>	50–60 Hz

#### PART NO.

DA16FS (3,000 K)	5112007100-001
DA16FS HO (3,000 K)	5112007100-015

#### SPARE PARTS

#### PART NO.

Cover (DA16FS)	7112000600
----------------	------------

#### EXTRAS

- > 120 V AC execution
- > 24 V DC execution
- > Dimmable
- > Different color temperatures

