



RECESSED MOUNTED CEILING LUMINAIRE FOR ACCOMMODATION AND PUBLIC AREAS

|                         |  |
|-------------------------|--|
| <b>Design</b>           | According to rules of maritime classification societies and relevant standards |
| <b>Housing</b>          | Galvanized steel, powder coated white (RAL9016)                                |
| <b>Diffuser</b>         | Clear polycarbonate, ice crystal structure                                     |
| <b>Mounting</b>         | Mounting set for ceilings 23–55 mm   |
| <b>Cable entry</b>      | 2 inlets for cables max. Ø 13 mm   |
| <b>Protection class</b> | IP20 / IP44 in conjunction with ceiling, IP20 with louver                      |
| <b>Weight</b>           | 5.5 kg   |
| <b>Light source</b>     | Linear LP LED modules  |
| <b>Wattage</b>          | Max. 40 W  |
| <b>CCT (color)</b>      | 3,000 K or 4,000 K   |
| <b>Luminous flux</b>    | 3,100 lm   |
| <b>CRI</b>              | ≥ 80   |
| <b>Voltage</b>          | 220–240 V AC   |
| <b>Frequency</b>        | 50–60 Hz   |

PART NO.

DE38L 5111009710-xxx

SPARE PARTS

PART NO.

Icecrystal cover (DE38L) 7931002100

EXTRAS

- > 120 V AC execution
- > 24 V DC execution
- > Dimmable
- > Emergency battery back-up
- > Different mounting sets
- > Different louvers and diffusers
- > 4 inlets for cables max. Ø 13 mm

