



CORNICE LUMINAIRE, LED, EFFICIENT LIGHTING FOR FLOOR AREAS, PASSAGE WAYS, CABINS AND ACCOMMODATION AREAS

<b>Design</b>	According to rules of maritime classification societies, additional VDE and IEC
<b>Housing</b>	Galvanized steel, powder coated white (RAL9016)
<b>End caps</b>	Polycarbonate, white
<b>Diffuser</b>	Polycarbonate, opal
<b>Mounting</b>	2 mounting holes, $\varnothing$ 5.5 mm
<b>Cable entry</b>	4 inlets for cables max. $\varnothing$ 11 mm
<b>Protection class</b>	IP20
<b>Weight</b>	1.3 kg
<b>Light source</b>	LED module
<b>Wattage</b>	Max. 10 W
<b>CCT (color)</b>	3,000 K
<b>Luminous flux</b>	1,300 lm
<b>CRI</b>	$\geq 80$
<b>Voltage</b>	220–240 V AC
<b>Frequency</b>	50–60 Hz

#### PART NO.

EL Flex S 5113003400-002

#### SPARE PARTS

#### PART NO.

Cover 7112037700

End cap 7503000800

#### EXTRAS

- > 120 V AC execution
- > Different color temperatures

