



CORNICE LUMINAIRE, LED, EFFICIENT LIGHTING FOR FLOOR AREAS, PASSAGE WAYS, CABINS AND ACCOMMODATION AREAS

| | |
|-------------------------|--|
| Design | According to rules of maritime classification societies and relevant standards |
| Housing | Galvanized steel, powder coated white (RAL9016) |
| End caps | Polycarbonate, white |
| Diffuser | Polycarbonate, opal or crystal |
| Mounting | 4 mounting holes, \varnothing 5.4 mm |
| Cable entry | 2 / 4 inlets for cables max. \varnothing 11 mm |
| Protection class | IP30 |
| Weight | 2.8 kg (1x 10 W) 3.0 kg (1x 20 W) |
| Light source | Linear LP LED module |
| Wattage | Max. 10 W / max. 20 W |
| CCT (color) | 3,000 K or 4,000 K |
| Luminous flux | 1,300 lm (10 W) 3,000 lm (20 W) |
| CRI | \geq 80 |
| Voltage | 220–240 V AC |
| Frequency | 50–60 Hz |

PART NO.

| | |
|-------------------|----------------|
| EL33S (max. 10 W) | 5113003100-xxx |
| EL33S (max. 20 W) | 5113003200-xxx |

SPARE PARTS

PART NO.

| | |
|---------------|------------|
| Opal cover | 7112006900 |
| Crystal cover | 7112006800 |
| End cap | 7503000300 |

EXTRAS

- > 120 V AC execution
- > With 2-pole-switch
- > Max. 10 W execution with battery back-up

