



ADJUSTABLE LED DOWNLIGHT WITH MAGNETIC COVER RING, APPLICABLE FOR PUBLIC AREAS, TILT +/-25° AND TURN 350°, FIXABLE POSITION

Design	According to rules of maritime classification societies and relevant standards
Housing	Polycarbonate, black
Decorative ring	White RAL9010 or chrome (has to be ordered separately)
Mounting	Fixing springs for ceilings max. 20 mm
Connection type	Connection cable with Wago 5-pole plug
Protection class	IP20
Weight	0.45 kg
Light source	LED module
Wattage	Max. 12 W
CCT (color)	3,000–2,000 K (DimToWarm)
Luminous flux	650 lm
CRI	≥ 80
Voltage	120–240 V AC
Frequency	50–60 Hz
Control mode	DIM 1–10 V (if dimming signal is not connected, output is 3,000 K with 650 lm)

PART NO.	BEAM	TYPE
5555000100-018	25°	flush
5555000100-019	40°	flush
5555000100-020	60°	flush
5556000100-019	25°	recessed
5556000100-020	40°	recessed
5556000100-021	60°	recessed

PART. NO.	RING	COLORS	TYPE
5532003100-001	RAL9010		flush
5532003100-002	Chrome		flush
5532003200-001	RAL9010		recessed
5532003200-002	Chrome		recessed

SPARE PARTS	PART NO.
Female connector Wago	7124003400

★ EXTRAS

- > Different connectors
- > Different finishes

