



FLAT SURFACE LED DOWNLIGHT FOR WALL AND CEILING MOUNTING, WITH CHANGEABLE COVER RING OF VARIOUS COLORS

<b>Design</b>	According to rules of maritime classification societies and relevant standards
<b>Housing</b>	Polycarbonate
<b>Decorative ring</b>	Steel (has to be ordered separately)
<b>Cover</b>	Polycarbonate, clear
<b>Mounting</b>	3 mounting holes, Ø 4.5 mm
<b>Connection type</b>	Contact plug / ceiling connector with Wago 3-pole plug (has to be ordered separately)
<b>Protection class</b>	IP20
<b>Weight</b>	0.28 kg
<b>Light source</b>	Cluster LP LED module
<b>Wattage</b>	Max. 10 W
<b>CCT (color)</b>	2,700 K
<b>Luminous flux</b>	450 lm
<b>CRI</b>	≥ 80
<b>Voltage</b>	220–240 V AC
<b>Frequency</b>	50–60 Hz

## PART NO.

DL170	5503000700-009
Ring RAL 9016	5532003800-005
Ring chrome	5532003800-004
Connector	5533001100-001

## ★ EXTRAS

- > Emergency light operation
- > Different connectors
- > Connector units for B0 / B15 application available
- > Different color temperatures
- > Different finishes

