



CHART TABLE LIGHT WITH FLEXIBLE ARM  
AND SWITCH IN BASE

|                         |                                                                                |
|-------------------------|--------------------------------------------------------------------------------|
| <b>Design</b>           | According to rules of maritime classification societies and relevant standards |
| <b>Housing</b>          | Metal / plastics, black                                                        |
| <b>Switch</b>           | In base                                                                        |
| <b>Flex arm</b>         | 500 mm                                                                         |
| <b>Mounting</b>         | Base mounting,<br>4 mounting holes $\varnothing$ 4.5 mm                        |
| <b>Connection type</b>  | Connection cable with plug                                                     |
| <b>Protection class</b> | IP20                                                                           |
| <b>Weight</b>           | 1.4 kg                                                                         |
| <b>Light source</b>     | MR16 LED                                                                       |
| <b>Lamp base</b>        | GU5.3                                                                          |
| <b>Wattage</b>          | Max. 3 W                                                                       |
| <b>CCT (color)</b>      | 5,500 K                                                                        |
| <b>Voltage</b>          | 230 V AC                                                                       |
| <b>Frequency</b>        | 50–60 Hz                                                                       |

## PART NO.

T114

5135007400-000

## SPARE PARTS

## PART NO.

Transformer 120 V / 12 V

7103009500

Transformer 230 V / 12 V

7103014600

## ★ EXTRAS

- > 24 V execution
- > Switch in pedestal
- > Jointed lamp head
- > IP65
- > Different arm lengths (250 mm / 700 mm)

