



EXPLOSION PROOF FLOODLIGHT,
MAX. 1X 250 W - 1X 600 W FOR HST/HIT LAMPS
WITH INTEGRATED BALLAST

Design	According to rules of maritime classification societies and relevant standards
Ex marking	II 2G Ex de IIB T2-T4 Gb II 2D Ex tb IIC T85°C-T210°C Db IP66
Housing	Copper-free aluminium with grey polyester paint finish
Cover	Borosilicate glass
Mounting	Stainless steel bracket, adjustable
Reflector	Aluminium anodized
Cable entry	2 cable entries M25 (one Ex-e cable gland, one plugged)
Connection type	Rubber cable H07RN-F 3G2.5, 20 meters
Protection class	IP66
Weight	31.0 kg
Light source	HST/HIT lamp (not included)
Lamp base	E40
Voltage	230 V AC
Frequency	50 HZ or 60 Hz

■ HST/HIT 250 W CODE PX 0425 PART NO.

Type	TA (GAS)	Temperature	
50 Hz	T3	-20°C - +55°C	5101001700-005
	T4	-20°C - +40°C	
60 Hz	T3	-20°C - +55°C	5101001700-001
	T4	-20°C - +40°C	

■ HST/HIT 400 W CODE PX 0440 PART NO.

Type	TA (GAS)	Temperature	
50 Hz	T3	-20°C - +55°C	5101001700-006
	T4	-20°C - +40°C	
60 Hz	T3	-20°C - +55°C	5101001700-002
	T4	-20°C - +40°C	

■ HST/HIT 600 W CODE PX 0460 PART NO.

Type	TA (GAS)	Temperature	
50 Hz	T2	-20°C - +55°C	5101001700-007
	T3	-20°C - +40°C	
60 Hz	T2	-20°C - +55°C	5101001700-003
	T3	-20°C - +40°C	

